



## EPT35-DP/SP

### Characteristics

- Electronic power steering system.
- Floating bodies with patent design.
- AC Driving system.
- Automatic lifting limit.
- Load backrest is standard.
- Side-way battery.
- Curve automatic deceleration more safe.
- Stepless speed control system.
- Emergency reversing device.
- Emergency brake switch.
- Battery:FAAM 330/490Ah.
- Options:Long or short forks.
- Options:Lithium battery.

Model		EPT35-DP	EPT35-SP	WPT35
Configuration No.		CBD35-510	CBD35-520	CBD35-530
Loading capacity	kg	3500	3500	3500
Load center	mm	2084	1602	1602
Operating type		Rider	Rider	Walkie
Wheels type		PU	PU	PU
Driving wheel size	mm	φ300×120	φ300×120	φ300×120
Max.lifting height	mm	145	145	145
Overall fork width	mm	680/180	680/220	680/220
Fork length	mm	2432	1212/1365/1517	1212/1365/1517
Fork width	mm	250	230	230
Fork thickness	mm	60	60	60
Overall length	mm	3605	2374	2222
Overall width	mm	930	930	832
Overall height(With handle)	mm	1536	1536	1536
Min.Turning radius	mm	2708	2190	2051
Min.Aisle width for pallets 1200×1200	mm	3650	2536	2365
Travel speed,laden/unladed	km/h	11/14	11/14	4/4.5
Lift speed,laden/unladed	mm/s	35/40	35/40	35/40
Gradeability,laden/unladed	%	5/12	5/12	5/10
Driving motor	kW	AC4.2	AC4.2	AC1.5
Lift motor	kW	DC2.2	DC2.2	DC2.2
Battery voltage/capacity	V/Ah	24/360	24/360	24/360
Controller		CURTIS	CURTIS	ZAPI
Battery weight	kg	302	302	302
Service weight with battery	kg	1146	1038	910

