



**Popular**

**◀ EPT30-EPS**

**Characteristics**

- Electronic power steering system.
- Floating bodies with patent design.
- AC Driving system.
- Automatic lifting limit.
- Side-way battery.
- Curve automatic deceleration devices.
- Stepless speed control system.
- Emergency reversing device.
- Emergency brake switch.
- Option: Lithium battery.

Model		EPT30-EPS
Configuration No.		CBD30-460
Loading capacity	kg	3000
Load center	mm	600
Operating type		Rider
Wheels type		PU
Driving wheel size	mm	φ248×75
Max.lifting height	mm	120
Overall fork width	mm	550/685
Fork length	mm	1150/1200
Fork width	mm	170
Fork thickness	mm	75
Overall length	mm	1916/2333
Overall width	mm	790
Overall height(With handle)	mm	1455
Min.Turning radius	mm	1746/2158
Min.Aisle width for pallets 1000×1200	mm	2077/2458
Travel speed,laden/unladed	km/h	6/6
Lift speed,laden/unladed	mm/s	30/35
Gradeability,laden/unladed	%	6/16
Driving motor	kW	AC1.5
Lift motor	kW	DC1.2
Battery voltage/capacity	V/Ah	24/270
Controller		GEOLIFT
Battery weight	kg	247
Service weight with battery	kg	831

