



EPT20-HS ▶



Characteristics

- High running speed 11km/h.
- EPS.
- AC Driving System.
- Electric Lifting.
- AC Controller.
- Forks fit for double-deck pallet.
- Option: 7km/h lower travel speed.
- Option: 320Ah Battery capacity.
- Side-way Battery.
- Option: Lithium battery.

Model		EPT20-HS
Configuration No.		CBD20-490
Loading capacity	kg	2000
Load center	mm	600
Operating type		Rider
Wheels type		PU
Driving wheel size	mm	φ248×75
Max.lifting height	mm	120
Overall fork width	mm	550/685
Fork length	mm	1150/1200
Fork width	mm	170
Fork thickness	mm	75
Overall length	mm	2465
Overall width	mm	790
Overall height(With handle)	mm	1172
Min.Turning radius	mm	2278
Min.Aisle width for pallets 1000×1200	mm	2589
Travel speed,laden/unladen	km/h	10/10
Lift speed,laden/unladen	mm/s	30/35
Gradeability,laden/unladen	%	10/15
Driving motor	kW	AC 3
Lift motor	kW	DC1.2
Battery voltage/capacity	V/Ah	24/280
Controller		GEOLIFT
Battery weight	kg	243
Service weight with battery	kg	840

